

**HIGH-GROUND**  
**Moving Yoke**

**TECHNICAL FEATURES**

**VOLTAGE: 230V 50 OR 60 HZ (ON REQUEST) OR 50/60 HZ SWITCHABLE VERSION**

**POWER CONSUMPTION: 2000W  $\text{COS}\phi \geq 0,9$**

**WEIGHT: 67KG**

**CONTROL SYSTEM REQUIRED: DMX 512**

**TOTAL DMX CHANNELS REQUIRED: 10 (12 EXTEND PERSONALITY)**

**STAND-ALONE PROGRAMMABLE BY THE DISPLAY IN THE BASE**

**8/16 BITS PAN/TILT RESOLUTION**

**MAX. PAN ANGLE: 540°**

**MAX. TILT ANGLE: 262°**

**PAN SPEED: 540° IN 3,2 SEC.**

**TILT SPEED: 262° IN 2,9 SEC.**

**IP RATE: 43 (WEATHERPROOF)**

**TYPE OF LAMP: OSRAM MaxiSharXS HTI 2000W/D10/60      LAMP LIFE: 750H**

**LAMP LUMINOUS FLUX: 200.000 Lumens**

**COLOURS: 5 + WHITE. RAINBOW EFFECT (ADJ. SPEED)**

**SHUTTER AND STROBO EFFECT FROM 1 TO 5 FLASHES/SEC.**

**ZOOM: FROM 1,8° TO 20°**

**ZOOM SPEED: FROM 1,8° TO 20° IN 500 MILLISEC, NO CROWN CIRCULAR PROJECTION**

**ZOOM AT MIN. - ILLUMINANCE: 26.100 LUX AT 25M COVERED AREA: 0,65x0,35M**

**ZOOM AT MAX. - ILLUMINANCE: 380 LUX AT 25M COVERED AREA Ø 9,5M**

ALL DATA CAN BE MODIFIED WITHOUT NOTICE

24/09/2009