

SUPER-NOVA
Moving Yoke

TECHNICAL FEATURES

VOLTAGE: 230V 50 OR 60 HZ (ON REQUEST) OR 50/60 HZ SWITCHABLE VERSION

POWER CONSUMPTION: 2000W $\text{COS}\varphi \geq 0,9$

WEIGHT: 67KG

CONTROL SYSTEM REQUIRED: DMX 512

TOTAL DMX CHANNELS REQUIRED: 15 (18 EXTENDED PERSONALITY)

STAND-ALONE PROGRAMMABLE BY THE DISPLAY IN THE BASE

8/16 BITS PAN/TILT RESOLUTION

MAX. PAN ANGLE: 540°

MAX. TILT ANGLE: 260°

PAN SPEED: 540° IN 3,2 SEC.

TILT SPEED: 260° IN 2,9 SEC.

IP RATE: 43 (WEATHERPROOF)

TYPE OF LAMP: OSRAM HTI 1200W/D7/60 AVERAGE LAMP LIFE: 750 H

LAMP LUMINOUS FLUX: 200.000 LUMENS

5 DIFFERENT LIGHTING EFFECTS

COLOURS: 6 + WHITE AND CMY COLOR MIXING

SHUTTER + DIMMER + STROBO

CONTROL AND STORAGE OF ANGULAR POSITION OF EACH REFLECTOR

CW-CCW ADJUSTABLE REFLECTOR'S ROTATION SPEED + STOP

BEAMS' APERTURE OF EACH REFLECTORS : 38°

E-Mail: info@novalight.it Internet : www.novalight.it